

J-series battery,D-series battery,M-series battery(4.5AH-3000AH)

J series battery:

UNIPOWER Model	voltage (V)	Capacity(AH)		Dimensions(mm)			Rserve Capacity(min)	CCA(A MP)-18 °C	Assembly Figures	Terminal Type	Weight WithAcid(Kgs)	Base Hold-downHD)	Equivalent Model
		20HR	5HR	L	W	TH							
J35 (L/R)	12	35	28	197	129	224	52	330	B1/B2	SMALL	11.00	NO	40B2 L/R
J35S (L/R)	12	35	28	197	129	224	80	330	B1/B2	STD	11.00	NO	40B2 L/RS
J45 (L/R)	12	45	36	238	134	225	80	550	B1/B2	SMALL	12.80	NO	55B24 L/R
J45S (L/R)	12	45	36	238	134	225	80	550	B1/B2	STD	12.08	NO	55B24 L/RS
J50 (L/R)	12	50	40	260	174	222	86	420	B1/B2	STD	15.00	NO	48D26 L/R
J60-55 (L/R)	12	60	48	260	174	222	108	525	B1/B2	STD	16.50	NO	55D26 L/R
J60(L/R)	12	60	48	232	173	226	100	500	B1/B2	STD	15.80	NO	55D23 L/R
J65(L/R)	12	65	52	232	173	226	110	580	B1/B2	STD	16.60	NO	70D23 L/R
J70/80 (L/R)	12	70	56	260	174	223	130	630	B1/B2	STD	17.50	NO	80D26 L/R
J70-65 (L/R)	12	70	56	304	173	225	136	630	B1/B2	STD	20.20	BHD	65D31 L/R
J90-75 (L/R)	12	75	60	304	173	225	150	735	B1/B2	STD	21.80	BHD	75D31 L/R
J90-95 (L/R)	12	90	72	304	173	225	160	850	B1/B2	STD	22.00	BHD	95D31 L/R
J100A (L/R)	12	100	80	330	173	232	182	870	B1/B2	STD	26.00	NO	GP31 L/RA
J100S (L/R)	12	100	80	330	173	232	182	870	B1/B2	STUD	26.00	NO	GP31L /RS

D series battery

UNIPOWER Model	Capacity (AH)	CA(AM)		Dimensions(mm)				Assembly Figures	Weight Width Acid(kg)	Terminal type	Equivalent Mode
		DIN	IEC	L	W	H	TH				
		(9.0V)	(8.4V)								
D45	45	220	250	249	175	160	180	B1	14	STD	54515
D54	54	260	310	275	175	175	175	B1	15	STD	55415
D55	55	255	295	243	175	190	190	B1	15.5	STD	55530
D63	63	300	350	293	175	175	175	B1	16	STD	56318
D66	66	300	350	300	175	190	190	B1	13.8	STD	56618
D85	85	450	520	354	175	175	175	B1	21	STD	58515
D88	88	395	440	378	175	190	190	B1	23	STD	588
D100	100	400	450	378	175	190	190	B1	34	STD	60038